

NEXT GENERATION POTS LINES

POTSCAST-2-LTE



TECHNICAL SPECIFICATIONS - PC222-LTE

General Information

- POTS Replacement Box
- Dimensions: 100 W x 200 H x 28.5 D
- Case: Metal
- WAN Ports: 1
- WAN (PoE): 48V / 24V / 12V
- WiFi: No
- WAN over WiFi: No
- LAN Ports: 1
- FXS Ports: 2
- Power Input: 24V DC
- No Battery Input

Capabilities

- Voice (VoIP): Yes
- Alarm (VoIP): Yes
- Alarm XMTR: Yes
- Elevator: Yes
- FAX (T.38): Yes
- FAX XMTR (Store & Forward): Yes
- Modem (MoIP): Yes

Accessories

- Power Supply: 24V (3 meter)
- 2 Cellular Antennas
- Mounting Screws

LTE & Connectivity

- LTE Module: Telit
- LTE Radio Category: Cat 4
- TAA Compliant: Yes
- SIM: 2 (Physical) & 1 (eSIM)

Features

- LCD Display
- LCD On/Off Button
- LED Indicator Lights
- On/Off Button
- Reset Button
- Dry Contact Interface

Battery Specifications

- Battery Type: Li-Ion
- Battery Specs: 4 Cells - 20Ah
- Standby Time: 24+ Hours
- Replaceable Internal Battery

Regulatory and Compliance

- Permitted under NFPA 72 (National Fire Protection Association)
- HIPAA Compliant
- PCI Compliant
- FCC Compliant
- UL Listed
- Managed Facilities Voice Network (MFVN)
- Approved for Fire/Life Safety applications, including elevators and alarm systems
- Tested and extensively accepted by leading fire and burglar panel manufacturers
- Verizon, AT&T, & T-Mobile Certified