

NEXT GENERATION POTS LINES

POTSCAST-2



TECHNICAL SPECIFICATIONS - PC222

General Information

- POTS Replacement Box
- Dimensions: 230 W x 143 H x 68 D
- Case: Metal
- WAN Ports: 2
- WAN (PoE): 48V / 24V / 12V
- WiFi: Yes
- WAN over WiFi: Yes
- LAN Ports: 2
- FXS Ports: 2
- Power Input: 24V DC

Capabilities

- Voice (VoIP): Yes
- Alarm (VoIP): Yes
- Alarm XMTR: Yes
- Elevator: Yes
- FAX (T.38): Yes
- FAX XMTR (Store & Forward): Yes
- Modem (MoIP): Yes

Accessories

- Power Supply: 24V (3 meter)
- Mounting Screws

Features

- LCD Display
- LCD On/Off Button
- LED Indicator Lights
- On/Off Button
- Reset Button
- Dry Contact Interface

Battery Specifications

- Battery Type: Li-Ion
- Battery Specs: 8 Cells - 40Ah
- Standby Time: 24+ Hours
- Replaceable Internal Battery

Regulatory and Compliance

- Permitted under NFPA 72 (National Fire Protection Association)
- HIPAA Compliant
- PCI Compliant
- FCC Compliant
- UL Listed
- Approved for Fire/Life Safety applications, including elevators and alarm systems
- Tested and extensively accepted by leading fire and burglar panel manufacturers